

**NEW**

Now with rotatable  
spring guide head



# CABLE PULLING SYSTEMS

For professional cable laying



Verbindungen mit **System**  
The **Power** of Partnership

**Klauke**<sup>®</sup>

## Cable pulling systems

The innovative generation of our cable pulling systems offers convincing quality and a host of ingenious details for professional cable laying. These products are set apart by their reliability and long service life.

### Dura Spinner

Cable pulling systems with the innovative, extremely robust, twisted polyester fish tape (3.0 mm dia.) and rotatable spring guide head. Versions: 20 and 30 m



#### Highlights

- Extremely robust fish tape for very narrow bending radii
- This product's high thrust makes it the ideal solution for laying additional cables
- New rotatable spring guide head
- Suitable for rigid and flexible conduits
- Tape pulled in and out very simply
- Can also be uncoiled on the floor
- Including accessories and spare parts
- Robust ABS housing
- No more broken tapes

The new generation of cable fish tapes

## Incredibly flexible, incredibly robust

#### Dura Spinner

| Part No. | Item  |
|----------|---|
| 52074656 | Dura Spinner 3 mm dia., 20 m version, including rotatable spring guide head |
| 52074657 | Dura Spinner 3 mm dia., 30 m version, including rotatable spring guide head |

#### Scope of supply



| Part No. | Item   | Qty. |
|----------|--|------|
| 52055263 | Rotatable spring guide head with eyelet, M4, 6 mm dia. | 1    |
| 52055266 | Tension head with eyelet, M4                           | 1    |
| 52055311 | Pulling aid 3–6 mm dia.                                | 1    |

#### Replacement tapes



| Part No. | Item   |
|----------|--|
| 52074654 | Dura Spinner replacement tape 3 mm dia., 20 m, including rotatable spring guide head |
| 52074655 | Dura Spinner 3 mm dia., 30 m, including rotatable spring guide head                  |

## Speedy Spinner

Cable pulling device with fibreglass fish tape 3 mm dia.  
Versions: 20, 30 and 40 m



### Highlights

- Unique, user-friendly design
- New rotatable spring guide head
- Fibreglass tapes pulled in and out very simply and quickly
- Can also be uncoiled from the floor
- One-handed operation
- Inc. accessory set and pulling aid
- Lengths: 20, 30 and 40 m
- Robust ABS plastic housing

The portable cable pulling device

## Incredibly easy to use

Speedy Spinner is extremely easy to handle. Cables are guaranteed to be laid quickly and trouble free, even in conduits with narrow radii.

### Fibreglass fish tape

| Part No. | Item   |
|----------|--|
| 52055298 | Fibreglass fish tape 3 mm dia., 20 m version |
| 52055299 | Fibreglass fish tape 3 mm dia., 30 m version |
| 52055300 | Fibreglass fish tape 3 mm dia., 40 m version |

### Scope of supply

|   |   |   |   |   |
|---|---|---|---|---|
|                  | 52055304<br> (1) | 52055264<br> (2) | 52055306<br> (3) | 52055307<br> (4) |
| 52055308<br> (5) | 52055309<br> (6) | 52055311<br> (7) | 52055310<br> (8) |   |

| Part No. | Item                             | Qty. | Fig. |
|----------|----------------------------------|------|------|
| 52055304 | Tension heads with eyelet M5     | 3    | (1)  |
| 52055305 | Spring guide head with eyelet M5 | 1    | (2)  |
| 52055306 | Spring guide head M5 – 10 mm     | 1    | (3)  |
| 52055307 | Spring guide head M5 – 13 mm     | 1    | (4)  |
| 52055308 | Start/end sleeves M5             | 3    | (5)  |
| 52055309 | Connecting sleeves               | 3    | (6)  |
| 52055311 | Pulling aid<br>3 - 6 mm dia.     | 1    | (7)  |
| 52055310 | Cable grip M5, 4 - 15 mm dia.    | 1    | (8)  |

### New items

| Part No. | Item                                       |
|----------|--|
| 52055264 | Rotatable spring guide head with eyelet M5 |



### Accessories

|   |   |   |   |
|---|---|---|---|
| 52055304<br> (1) | 52055308<br> (5) | 52055309<br> (6) | 52055311<br> (7) |
|---|---|---|---|

| Part No.       | Item                         | Qty. | Fig. |
|----------------|------------------------------|------|------|
| 52055303       | 10-part accessory set        |      |      |
| Consisting of: |                              |      |      |
| 52055304       | Tension heads with eyelet M5 | 3    | (1)  |
| 52055308       | Start/end sleeves M5         | 3    | (5)  |
| 52055309       | Connecting sleeves           | 3    | (6)  |
| 52055311       | Pulling aid<br>3 - 6 mm dia. | 1    | (7)  |



| Part No. | Item   |
|----------|--|
| 52055289 | Fibreglass replacement tape, 3 mm dia., 20 m |
| 52055290 | Fibreglass replacement tape, 3 mm dia., 30 m |
| 52055291 | Fibreglass replacement tape, 3 mm dia., 40 m |


## The Easy Roller series Incredibly flexible

Highly resistant yet lightweight, making easy work of transporting the Easy Roller. And not only that: The bearings with low friction losses and side guides integrated into the rollers make it much easier to coil and uncoil large cable drums. The shallow incline of the ramp allows the cable drum to be positioned without any effort. And another benefit: The rollers can be flexibly adjusted to the cable drum diameter.


### Easy Roller



Flexible adjustment to the cable drum diameter



Ramp with shallow incline for easy coiling and uncoiling of the cable drum



#### Easy Roller

| Part No. | Item                 | Drum dia. mm | Dimensions mm  | Load Kg | Weight Kg | Material |
|----------|----------------------|--------------|----------------|---------|-----------|----------|
| 52055383 | Easy Roller Standard | 200 - 700    | 530 x 570 x 90 | 200     | 10        | Steel    |
| 52055384 | Easy Roller Wide     | 200 - 700    | 670 x 605 x 95 | 250     | 11        | Steel    |

#### Highlights


- Highly robust, lightweight version
- 30% lighter than conventional cable drum roller, one of the lowest weight rollers on the market
- Ramp with shallow incline for simple uncoiling and coiling of the cable drum
- The rollers can be adjusted to the cable drum diameter
- Rollers with integrated side guides
- Use of high-quality bearings for fast and simple uncoiling of the drum

### Easy Roller Plus

Three different versions of cable drum uncoilers  
Consisting of two cable drum uncoiling rails and one spacer rail



Ball bearing mounted rollers



Reduced incline



#### Easy Roller Plus


| Part No. | Item                 | Drum dia. mm | Dimensions mm    | Load kg | Weight kg | Material  |
|----------|----------------------|--------------|------------------|---------|-----------|-----------|
| 52055401 | Easy Roller Plus S   | 400 - 1200   | 950 x 145 x 110  | 1000    | 33.5      | Steel     |
| 52055402 | Easy Roller Plus L   | 400 - 1800   | 1050 x 145 x 110 | 1000    | 35.5      | Steel     |
| 52055403 | Easy Roller Plus ALS | 400 - 1200   | 950 x 145 x 110  | 1000    | 19.5      | Aluminium |

#### Highlights

- Reduced incline of the ramp for simple loading of the cable drum
- Handles for easy positioning and carrying
- Ball bearing mounted rollers
- U-sections for fixing the uncoiling rails


Polyester Butler

Polyester cable pulling system with rotatable spring guide head and steel reel basket



Smart Butler

Fibreglass cable pulling system with steel reel basket and accessories



Highlights

- Unique design, galvanised and painted
- Highly robust construction
- Accessories mounted to the Polyester Butler itself
- Teflon extension connector for low friction when uncoiling and coiling
- Effective locking brake (wheel blocked at ¼ revolution)
- Ball bearing mounted for low-friction uncoiling and coiling
- With rotatable spring guided head

Highlights

- Unique design, galvanised and painted
- Highly robust construction
- Accessories mounted to the Smart Butler itself
- Teflon extension connector for low friction when uncoiling and coiling
- Effective locking brake (wheel blocked at ¼ revolution)
- Ball bearing mounted for low-friction uncoiling and coiling

The mobile cable pulling-in device  
Incredibly versatile

No matter whether you want to install conductors in industrial buildings or need to lay earth cables - the stable tubular steel, floor-mounted Smart Butler offers a diverse range of applications. It does everything for you and follows you wherever you go. And the best thing: The high-quality, ingenious details such as the Teflon® adapter and handy accessories make operations more efficient from the word go.



**Smart Butler**  
Version  
with rollers



**Smart Butler**  
Version  
without rollers



**Polyester Butler**  
Version only  
without rollers


**Smart Butler**

| Steel reel basket dia. mm | Fish tape dia. mm | Length m | Part No. | Suitable replacement tapes |
|---------------------------|-------------------|----------|----------|----------------------------|
| 330                       | 4.5               | 40       | 52055313 | 52055317                   |
|                           |                   | 60       | 52055315 | 52055318                   |
|                           |                   | 80       | 52055316 | 52055319                   |
| 550                       | 6                 | 40       | 52055325 | 52055329                   |
|                           |                   | 60       | 52055326 | 52055330                   |
|                           |                   | 80       | 52055327 | 52055331                   |
|                           |                   | 100      | 52055328 | 52055332                   |
|                           |                   | 40       | 52055337 | 52055342                   |
|                           |                   | 60       | 52055338 | 52055343                   |
| 660                       | 7.5               | 80       | 52055339 | 52055344                   |
|                           |                   | 100      | 52055340 | 52055345                   |
|                           |                   | 120      | 52055341 | 52055346                   |
| 790                       | 9                 | 40       | 52055347 | 52055353                   |
|                           |                   | 60       | 52055348 | 52055354                   |

| Steel reel basket dia. mm | Fish tape dia. mm | Length m | Part No. | Suitable replacement tapes |
|---------------------------|-------------------|----------|----------|----------------------------|
| 790                       | 9                 | 80       | 52055349 | 52055355                   |
|                           |                   | 100      | 52055350 | 52055356                   |
|                           |                   | 120      | 52055351 | 52055357                   |
|                           |                   | 150      | 52055352 | 52055358                   |
|                           |                   | 150      | 52055359 | 52055363                   |
|                           |                   | 200      | 52055360 | 52055364                   |
| 1000                      | 11                | 250      | 52055361 | 52055365                   |
|                           |                   | 300      | 52055362 | 52055366                   |

**Polyester Butler**

| Steel reel basket dia. mm | Fish tape dia. mm | Length m | Part No. |
|---------------------------|-------------------|----------|----------|
| 350                       | 6                 | 50       | 52074658 |



**Smart Butler scope of supply**

| Fish tape dia. mm | Part No. | Item   | Qty. | Fig. |
|-------------------|----------|--|------|------|
| 4.5               | 52055321 | Start/end sleeve WW 1/4"                             | 1    | (1)  |
|                   | 52055323 | Starting spinner with shackle WW 1/4"                | 1    | (2)  |
|                   | 52055320 | Tension head with eyelet WW 1/4" for 4.5 - 6 mm dia. | 1    | (3)  |
|                   | 52055322 | Connecting sleeve                                    | 1    | (4)  |
| 6                 | 52055333 | Start/end sleeve WW 1/4"                             | 1    | (1)  |
|                   | 52055335 | Starting spinner with shackle WW 1/4"                | 1    | (2)  |
|                   | 52055320 | Tension head with eyelet WW 1/4" for 4.5 - 6 mm dia. | 1    | (3)  |
| 7.5               | 52055334 | Connecting sleeve                                    | 1    | (4)  |
|                   | 52055369 | Crimped with start/end sleeve                        | 1    | (1)  |
|                   | 52055367 | Starting spinner with shackle                        | 1    | (2)  |
| 9                 | 52056116 | Connecting sleeve WW 1/2" M12                        | 1    | (4)  |
|                   | 52055368 | Starting spinner with guide roller                   | 1    | (5)  |
|                   | 52055370 | Crimped with start/end sleeve                        | 1    | (1)  |
| 11                | 52055367 | Starting spinner with shackle                        | 1    | (2)  |
|                   | 52055372 | Connecting sleeve WW 1/2" M12                        | 1    | (4)  |
|                   | 52055368 | Starting spinner with guide roller                   | 1    | (5)  |
|                   | 52055371 | Crimped with start/end sleeve                        | 1    | (1)  |
|                   | 52055367 | Starting spinner with shackle                        | 1    | (2)  |
|                   | 52056117 | Connecting sleeve WW 1/2" M12                        | 1    | (4)  |
|                   | 52055368 | Starting spinner with guide roller                   | 1    | (5)  |

**Polyester Butler scope of supply**

| Fish tape dia. mm | Part No. | Item  | Qty. | Fig. |
|-------------------|----------|---|------|------|
| 6                 | 52055321 | Start/end sleeve WW 1/4"                              | 1    | (1)  |
|                   | 52055323 | Starting spinner with shackle WW 1/4"                 | 1    | (2)  |
|                   | 52055320 | Tension head with eyelet WW 1/4" for 4.5 - 6 mm dia.  | 1    | (3)  |
|                   | 52055265 | Rotatable spring guide head with eyelet M5, 8 mm dia. | 1    | (6)  |



Smart Butler also available with counter, Part No. suffix "C"

### Polyester fish tapes

4.5 mm dia. with screw-off M5 start/end sleeve, spring guided head and pulling aid




#### Highlights

- 50% less friction than nylon tapes
- Replaceable spring guided head and eyelet
- Pulling aid supplied as standard
- Extremely flexible and practically unbreakable
- Lengths: 10/15/20/25/30 m

#### Polyester fish tape

| Part No. | Item  |
|----------|---|
| 52055292 | Polyester fish tape green 4.5 mm dia., 10 m |
| 52055293 | Polyester fish tape green 4.5 mm dia., 15 m |
| 52055294 | Polyester fish tape green 4.5 mm dia., 20 m |
| 52055295 | Polyester fish tape green 4.5 mm dia., 25 m |
| 52055296 | Polyester fish tape green 4.5 mm dia., 30 m |

#### Accessories



| Part No. | Item  |      |      |
|----------|---|------|------|
| 52055396 | Accessory set (5 part) for polyester fish tapes |      |      |
| Part No. | Consisting of:                                  | Qty. | Fig. |
| 52055398 | Tension heads with eyelet M5                    | 2    | (1)  |
| 52055397 | Spring guide head with eyelet M5                | 2    | (2)  |
| 52055311 | Pulling aid                                     | 1    | (3)  |

| Part No. | Item   | Fig. |
|----------|--|------|
| 52055264 | Rotatable spring guided head with eyelet M5, 7 mm dia. | (4)  |

### Perlon® fish tapes

4 mm dia. with crimped M4 initial piece, screw-off spring guided head and eyelet

#### Perlon fish tape

| Part No. | Item                             |
|----------|----------------------------------|
| 52055276 | Perlon fish tape 4 mm dia., 5 m  |
| 52055277 | Perlon fish tape 4 mm dia., 10 m |
| 52055278 | Perlon fish tape 4 mm dia., 15 m |
| 52055279 | Perlon fish tape 4 mm dia., 20 m |
| 52055280 | Perlon fish tape 4 mm dia., 25 m |
| 52055281 | Perlon fish tape 4 mm dia., 30 m |

#### Accessories

| Part No. | Item  |
|----------|---|
| 52055288 | Spare parts for Perlon fish tapes, spring guide head M4, eyelet |



### Nylon fish tapes

4 mm dia. with spring guided head and eyelet

#### Nylon fish tape

| Part No. | Item   |
|----------|--|
| 52055270 | Nylon fish tape 4 mm dia., 5 m   |
| 52055271 | Nylon fish tape 4 mm dia., 10 m  |
| 52055272 | Nylon fish tape 4 mm dia., 15 m  |
| 52055273 | Nylon fish tape 4 mm dia., 20 m  |
| 52055274 | Nylon fish tape 4 mm dia., 25 m  |
| 52055275 | Nylon fish tape 4 mm dia., 30 m  |
| 52055260 | Nylon fish tape 4 mm dia., 10 m Including rotatable spring guided head |
| 52055261 | Nylon fish tape 4 mm dia., 20 m Including rotatable spring guided head |
| 52055262 | Nylon fish tape 4 mm dia., 30 m Including rotatable spring guided head |

#### Accessories



| Part No. | Item  |
|----------|---|
| 52055263 | Rotatable spring guided head with eyelet, M4, 6 mm dia. |



### Steel fish tapes

4 mm dia. with crimped M4 spring guided head and eyelet

#### Steel fish tape

| Part No. | Item                            |
|----------|---------------------------------|
| 52055283 | Steel fish tape 4 mm dia., 10 m |
| 52055285 | Steel fish tape 4 mm dia., 20 m |



## Cable installation lubricant

### Cable lubricant, liquid

for optical fibres and heavy cables



| Part No. | Content kg |
|----------|------------|
| 52055381 | 5          |
| 52055382 | 10         |

### Lubricating foam bottle

for large cable diameters in the electrical installation sector of trade and industry



| Part No. | Content kg |
|----------|------------|
| 52055380 | 1          |

### Lubricant spray

for electrical installation in 16 - 25 mm dia. pipes, non-flammable



| Part No. | Content ml |
|----------|------------|
| 52055378 | 400        |

### Cable lubricant gel

in tube for electrical installations in 16 - 25 mm dia. pipes



| Part No. | Content kg |
|----------|------------|
| 52055379 | 0.25       |

### Highlights

- For electrical/telephone cables in 16 – 150 mm pipes
- Reduces friction by up to 80 %
- Biodegradable
- Silicon-free
- Lubricating foam spray with non-flammable propellant

### Application examples:

| Type                    | Tape dia. | Pipe dia. | Thrust | Min. curve radius | Breaking strength | Tensile force with start/end sleeve | Recommended length |
|-------------------------|-----------|-----------|--------|-------------------|-------------------|-------------------------------------|--------------------|
|                         |           |           |        |                   |                   |                                     |                    |
|                         | mm        | mm        | kg     | mm                | kg                | kg                                  | m                  |
| <b>Fibreglass</b>       |           |           |        |                   |                   |                                     |                    |
| <b>Speedy Spinner</b>   | 3         | 16 - 32   | +++    | 160               | 400               | 110                                 | 20-30              |
|                         | 4.5       | 40 - 60   | +++    | 310               | 1200              | >200                                | 40-80              |
|                         | 6         | 50 - 80   | +++    | 400               | 2000              | >300                                | 40-110             |
| <b>Smart Butler</b>     | 7.5       | 63 - 100  | +++    | 500               | 3000              | >400                                | 40-120             |
|                         | 9         | 63 - 125  | +++    | 620               | 4500              | >500                                | 40-150             |
|                         | 11        | 63 - 150  | +++    | 770               | 7500              | >700                                | 150-300            |
| <b>Polyester</b>        |           |           |        |                   |                   |                                     |                    |
| <b>Dura Spinner</b>     | 3         | 16 - 40   | +++    | 50                | 300               | 100                                 | 20-30              |
| <b>Polyester Butler</b> | 6         | 40 - 60   | +++    | 160               | 600               | 300                                 | 50                 |
| <b>Nylon, Perlon®</b>   |           |           |        |                   |                   |                                     |                    |
|                         | 4         | 16 - 25   | +      | 80                | 280               | 120                                 | 10-20              |
| <b>Steel</b>            |           |           |        |                   |                   |                                     |                    |
|                         | 4         | 16 - 25   | +      | 100               | 900               | 115                                 | 10-20              |



[www.klauke.com](http://www.klauke.com)



**Klauke**<sup>®</sup>

**Gustav Klauke GmbH**  
Auf dem Knapp 46  
D-42855 Remscheid

Phone: +49 (0) 2191 / 907 - 0  
E-mail: [Klauke-Info@Emerson.com](mailto:Klauke-Info@Emerson.com)  
Internet: [www.klauke.com](http://www.klauke.com)

  
**EMERSON**

© 2019 Gustav Klauke GmbH. All rights reserved. Subject to change without notice. The Emerson logo and the Klauke logo are registered trade marks of Emerson Electric Co. in the USA and other countries. BRKES19GB 3.000 04/19 1